

BCC-4		BCL-4		BCCD-6		BCLD-6	
BCC-6		BCL-6		BCCD-8		BCLD-8	
BCC-8		BCL-8					

Cubetas GN incluidas en el precio - GN containers included in price

### Características técnicas - Technical data

ref.	largo length (mm)	alto height (mm)	fondo depth (mm)	base platos dish area (mm)	GN 1/3-40	potencia frig. frig. power (W)	consumo consumption (W)	tensión monofásica single phase voltage	refrigerante coolant
BCC-4	1050	255	410		4	160	200	230 V - 50 Hz	R-134a
BCC-6	1400	255	410		6	160	220	230 V - 50 Hz	R-134a
BCC-8	1755	255	410		8	160	240	230 V - 50 Hz	R-134a
BCL-4	1050	255	410	300 x 675		160	200	230 V - 50 Hz	R-134a
BCL-6	1400	255	410	300 x 1030		160	220	230 V - 50 Hz	R-134a
BCL-8	1755	255	410	300 x 1380		160	240	230 V - 50 Hz	R-134a
BCCD-6	1400	400	410		6	160	220	230 V - 50 Hz	R-134a
BCCD-8	1750	400	410		8	160	240	230 V - 50 Hz	R-134a
BCLD-6	1400	400	410	300 x 1030		160	220	230 V - 50 Hz	R-134a
BCLD-8	1750	400	410	300 x 1380		160	240	230 V - 50 Hz	R-134a

Características técnicas y constructivas sujetas a variación sin previo aviso.

We reserve the right to change specifications without prior notice.

- Exterior en acero inox AISI-304 18/10
- Fondo interior embutido en acero inox AISI 304 18/10
- Cristal curvo templado y securizado
- Iluminación por LEDS
- Puertas transparentes correderas
- BCCD y BCLD con estante superior no refrigerado
- Aislamiento de poliuretano inyectado, densidad 40 Kg/m<sup>3</sup>, cero efectos ODP y GWP
- Reguladores de altura
- Iluminación interior
- Unidad condensadora ventilada
- Ajuste de temperatura y descarche por control electrónico digital
- Temperatura de trabajo +4° +8° a 32°C de ambiente

- AISI-304 18/10 stainless steel exterior
- AISI-304 18/10 stainless steel stamped bottom
- Toughened curved safety glass
- LED lighting
- Transparent sliding doors
- BCCD and BCLD with no refrigerated glass shelf
- 40 Kg/m<sup>3</sup> density polyurethane insulation, zero ODP and GWP
- Adjustable supports
- Interior lighting
- Fan assisted condenser unit
- Temperature and defrost sets by digital electronic control
- Operating temperature +4° +8° , 32°C ambient

BCC - BCCD Bandeja interior embutida, preparada para cubetas GN1/3-40 (incluidas)






BCC - BCCD, stamped steel bottom, GN 1/3-40 containers capacity (included)

BCL - BCLD Bandeja interior embutida, preparada para platos (no incluidos)

BCL - BCLD, stamped steel (not GN capacity)

230v 60Hz / 115v 60Hz

consultar - consult



BCCD - 8



all photos must be considered as a reference - fotografías no contractuales



BCC - 6



BCL - 6

