

» Counter Bottle Coolers



CBC210G

- Fan assisted cooling
- 2 Glass doors
- Stainless steel interior
- 4 Adjustable stainless steel shelves
- Adjustable feet



Stainless steel shelves



CBC310G

- Internal LED light
- Fan assisted cooling
- 3 Glass doors
- Stainless steel interior
- 6 Adjustable stainless steel shelves
- Adjustable feet



CBC410G

- Internal LED light
- Fan assisted cooling
- 4 Glass doors
- Stainless steel interior
- 8 Adjustable stainless steel shelves
- Adjustable feet

Technical specifications

| Model | CBC210G | CBC310G | CBC410G |
|-----------------------------|-------------------|-------------------|--------------------|
| Climate Class | N | N | N |
| Temperature Range, °C | 2 to 10 | 2 to 10 | 2 to 10 |
| Gross Volume, l | 290 | 460 | 630 |
| Net Volume, l | 277 | 442 | 605 |
| Cans, 330 ml | - | - | - |
| Cans, 500 ml | - | - | - |
| Bottles, 330 ml | - | - | - |
| Bottles, 1,5 l PET | - | - | - |
| External Dimensions, WxDxH | 1462x513x860 | 2002x513x860 | 2542x513x860 |
| Internal Dimensions, WxDxH | 1082x415x760 | 1622x415x760 | 2162x415x760 |
| Doors | 2 hinged glass | 3 hinged glass | 4 hinged glass |
| Shelves/Baskets | 4, SS304 | 6, SS304 | 8, SS304 |
| Outer Body | Black, RAL9011 | Black, RAL9011 | Black, RAL9011 |
| Interior | SS430 | SS430 | SS430 |
| Castors/Feet | 6 adjustable feet | 8 adjustable feet | 10 adjustable feet |
| Lock | Y | Y | Y |
| Voltage/Frequency, V/Hz | 220-240/50 | 220-240/50 | 220-240/50 |
| Input Power, W | 250 | 250 | 350 |
| Energy Consumption, kWh/24h | | | |
| Gross Weight, kg | 121,5 | 154 | 171 |
| Net Weight, kg | 100 | 125 | 150 |
| Noise Level dbA | 42 | 42 | 44 |
| Type of Cooling | Fan assisted | Fan assisted | Fan assisted |
| Type of Defrost | Automatic | Automatic | Automatic |
| Controller | Digital | Digital | Digital |
| Thermometer | Y | Y | Y |
| Refrigerant | R134a | R134a | R134a |
| Charge, g | 150 | 160 | 190 |
| Internal Light | LED | LED | LED |

» Counter Bottle Coolers



CBC220

- Fan assisted cooling
- 1 Solid door
- 2 Drawers
- Stainless steel interior
- 2 Adjustable stainless steel shelves
- Adjustable feet



Combinations of drawers and doors are easily made as doors and drawers are provided as separate kits



CBC210

- Fan assisted cooling
- 2 Solid doors
- Stainless steel interior
- 4 Adjustable stainless steel shelves
- Adjustable feet



CBC240

- Fan assisted cooling
- 4 Drawers
- Stainless steel interior
- Adjustable feet

Technical specifications

| Model | CBC210 | CBC220 | CBC240 |
|-----------------------------|-------------------|-------------------|-------------------|
| Climate Class | N | N | N |
| Temperature Range, °C | 2 to 10 | 2 to 10 | 2 to 10 |
| Gross Volume, l | 290 | 290 | 290 |
| Net Volume, l | 277 | 277 | 277 |
| Cans, 330 ml | - | - | - |
| Cans, 500 ml | - | - | - |
| Bottles, 330 ml | - | - | - |
| Bottles, 1,5 l PET | - | - | - |
| External Dimensions, WxDxH | 1462x513x860 | 1462x513x860 | 1462x513x860 |
| Internal Dimensions, WxDxH | 1082x415x760 | 1082x415x760 | 1082x415x760 |
| Doors | 2 hinged solid | 1 door, 2 drawers | 4 drawers |
| Shelves/Baskets | 4, SS304 | 2, SS304 | 0 |
| Outer Body | Black, RAL9011 | Black, RAL9011 | Black, RAL9011 |
| Interior | SS430 | SS430 | SS430 |
| Castors/Feet | 6 adjustable feet | 6 adjustable feet | 6 adjustable feet |
| Lock | Y | Y | N |
| Voltage/Frequency, V/Hz | 220-240/50 | 220-240/50 | 220-240/50 |
| Input Power, W | 250 | 250 | 250 |
| Energy Consumption, kWh/24h | | | |
| Gross Weight, kg | 110,5 | - | - |
| Net Weight, kg | 89 | - | - |
| Noise Level dbA | 42 | 42 | 42 |
| Type of Cooling | Fan assisted | Fan assisted | Fan assisted |
| Type of Defrost | Automatic | Automatic | Automatic |
| Controller | Digital | Digital | Digital |
| Thermometer | Y | Y | Y |
| Refrigerant | R134a | R134a | R134a |
| Charge, g | 150 | 150 | 150 |
| Internal Light | LED | LED | LED |

» Counter Bottle Coolers



CBC320

- Internal LED light
- Fan assisted cooling
- 2 Solid doors
- 2 Drawers
- Stainless steel interior
- 6 Adjustable stainless steel shelves
- Adjustable feet



CBC310

- Fan assisted cooling
- Solid doors
- Stainless steel interior
- 6 Adjustable stainless steel shelves
- Adjustable feet



CBC360

- Internal LED light
- Fan assisted cooling
- 6 Drawers
- Stainless steel interior
- Adjustable feet

Technical specifications

| Model | CBC310 | CBC320 | CBC340 | CBC360 |
|-----------------------------|-------------------|--------------------|-------------------|-------------------|
| Climate Class | N | N | N | N |
| Temperature Range, °C | 2 to 10 | 2 to 10 | 2 to 10 | 2 to 10 |
| Gross Volume, l | 460 | 460 | 460 | 460 |
| Net Volume, l | 442 | 442 | 442 | 442 |
| Cans, 330 ml | - | - | - | - |
| Cans, 500 ml | - | - | - | - |
| Bottles, 330 ml | - | - | - | - |
| Bottles, 1,5 l PET | - | - | - | - |
| External Dimensions, WxDxH | 2002X513X860 | 2002X513X860 | 2002X513X860 | 2002X513X860 |
| Internal Dimensions, WxDxH | 1622X415X760 | 1622X415X760 | 1622X415X760 | 1622X415X760 |
| Doors | 3 hinged solid | 2 doors, 2 drawers | 1 door, 4 drawers | 6 drawers |
| Shelves/Baskets | 6, SS304 | 4, SS304 | 2, SS304 | 0 |
| Outer Body | Black, RAL9011 | Black, RAL9011 | Black, RAL9011 | Black, RAL9011 |
| Interior | SS430 | SS430 | SS430 | SS430 |
| Castors/Feet | 8 adjustable feet | 8 adjustable feet | 8 adjustable feet | 8 adjustable feet |
| Lock | Y | Y | Y | N |
| Voltage/Frequency, V/Hz | 220-240/50 | 220-240/50 | 220-240/50 | 220-240/50 |
| Input Power, W | 250 | 250 | 250 | 250 |
| Energy Consumption, kWh/24h | | | | |
| Gross Weight, kg | 139 | - | - | - |
| Net Weight, kg | 106 | - | - | - |
| Noise Level dbA | 42 | 42 | 42 | 42 |
| Type of Cooling | Fan assisted | Fan assisted | Fan assisted | Fan assisted |
| Type of Defrost | Automatic | Automatic | Automatic | Automatic |
| Controller | Digital | Digital | Digital | Digital |
| Thermometer | Y | Y | Y | Y |
| Refrigerant | R134a | R134a | R134a | R134a |
| Charge, g | 160 | 160 | 160 | 160 |
| Internal Light | LED | LED | LED | LED |

» Counter Bottle Coolers



CBC440

- Internal LED light
- Fan assisted cooling
- 2 Solid doors
- 4 Drawers
- Stainless steel interior
- 4 Adjustable stainless steel shelves
- Adjustable feet



CBC410

- Internal LED light
- Fan assisted cooling
- 4 Solid doors
- Stainless steel interior
- 8 Adjustable stainless steel shelves
- Adjustable feet



CBC480

- Internal LED light
- Fan assisted cooling
- 8 Drawers
- Stainless steel interior
- Adjustable feet

Technical specifications

| Model | CBC410 | CBC420 | CBC440 | CBC460 | CBC480 |
|-----------------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| Climate Class | N | N | N | N | N |
| Temperature Range, °C | 2 to 10 | 2 to 10 | 2 to 10 | 2 to 10 | 2 to 10 |
| Gross Volume, l | 630 | 630 | 630 | 630 | 630 |
| Net Volume, l | 605 | 605 | 605 | 605 | 605 |
| Cans, 330 ml | - | - | - | - | - |
| Cans, 500 ml | - | - | - | - | - |
| Bottles, 330 ml | - | - | - | - | - |
| Bottles, 1,5 l PET | - | - | - | - | - |
| External Dimensions, WxDxH | 2542x513x860 | 2542x513x860 | 2542x513x860 | 2542x513x860 | 2542x513x860 |
| Internal Dimensions, WxDxH | 2162x415x760 | 2162x415x760 | 2162x415x760 | 2162x415x760 | 2162x415x760 |
| Doors | 4 hinged solid | 3 doors, 2 drawers | 2 doors, 4 drawers | 1 door, 6 drawers | 8 drawers |
| Shelves/Baskets | 8, SS304 | 6, SS304 | 4, SS304 | 2, SS304 | 0 |
| Outer Body | Black, RAL9011 | Black, RAL9011 | Black, RAL9011 | Black, RAL9011 | Black, RAL9011 |
| Interior | SS430 | SS430 | SS430 | SS430 | SS430 |
| Castors/Feet | 10 adjustable feet | 10 adjustable feet | 10 adjustable feet | 10 adjustable feet | 10 adjustable feet |
| Lock | Y | Y | Y | Y | N |
| Voltage/Frequency, V/Hz | 220-240/50 | 220-240/50 | 220-240/50 | 220-240/50 | 220-240/50 |
| Input Power, W | 350 | 350 | 350 | 350 | 350 |
| Energy Consumption, kWh/24h | | | | | |
| Gross Weight, kg | 144 | - | - | - | - |
| Net Weight, kg | 123 | - | - | - | - |
| Noise Level dbA | 44 | 44 | 44 | 44 | 44 |
| Type of Cooling | Fan assisted | Fan assisted | Fan assisted | Fan assisted | Fan assisted |
| Type of Defrost | Automatic | Automatic | Automatic | Automatic | Automatic |
| Controller | Digital | Digital | Digital | Digital | Digital |
| Thermometer | Y | Y | Y | Y | Y |
| Refrigerant | R134a | R134a | R134a | R134a | R134a |
| Charge, g | 190 | 190 | 190 | 190 | 190 |
| Internal Light | LED | LED | LED | LED | LED |