



Gastronomy

700_{PC}

	Modello Model	Codice Code	Gas / Gas		Range °C	Porta	
				gr	Range °C	Door	
	GREEN PLUS 700 TN	7G070INC2A001	R290	90	-2/+7°	1 CIECA/FULL	
	GREEN 700 TN	7G070INC4A001	R404a	260	-2/+7°	1 CIECA/FULL	
	GREEN 700 TN R**	7G070RNC4A001	R404a		-2/+7°	1 CIECA/FULL	
	UC700TN*	74861752	R404a				
	GREEN PLUS 700 BT	7G070IBC2A001	R290	100	-24/-10°	1 CIECA/FULL	
	GREEN 700 BT	7G070IBC4A001	R404a	350	-24/-10°	1 CIECA/FULL	
	GREEN 700 BT R**	7G070RBC4A001	R404a		-24/-10°	1 CIECA/FULL	
	UC700BT*	74861762	R404a				
		GREEN PLUS 700 TN 2P	7G070INC2A002	R290	90	-2/+7°	2 CIECHE/FULL
		GREEN 700 TN 2P	7G070INC4A002	R404a	260	-2/+7°	2 CIECHE/FULL
		GREEN 700 TN 2P R**	7G070RNC4A002	R404a		-2/+7°	2 CIECHE/FULL
		UC700TN*	74861752	R404a			
	GREEN PLUS 700 BT 2P	7G070IBC2A002	R290	100	-24/-10°	2 CIECHE/FULL	
	GREEN 700 BT 2P	7G070IBC4A002	R404a	350	-24/-10°	2 CIECHE/FULL	
	GREEN 700 BT 2P R**	7G070RBC4A002	R404a		-24/-10°	2 CIECHE/FULL	
	UC700BT*	74861762	R404a				
	GREEN 700 TN/TN	7G072ITC4A001	R404a	220/220	-2/+7° -2/+7°	2 CIECHE/FULL	
	GREEN 700 TN/TN R**	7G072RTC4A001	R404a		-2/+7° -2/+7°	2 CIECHE/FULL	
	UC350TN*	74861750 x 2	R404a				
	GREEN 700 BT/BT	7G072ITC4A002	R404a	270/270	-24/-10° -24/-10°	2 CIECHE/FULL	
	GREEN 700 BT/BT R**	7G072RTC4A002	R404a		-24/-10° -24/-10°	2 CIECHE/FULL	
	UC350BT*	74861760 x 2	R404a				
	GREEN 700 TN/BT	7G072ITC4A003	R404a	220/270	-2/+7° -24/-10°	2 CIECHE/FULL	
	GREEN 700 TN/BT R**	7G072RTC4A003	R404a		-2/+7° -24/-10°	2 CIECHE/FULL	
	UC350TN*	74861750	R404a				
	UC350BT*	74861760	R404a				
		74703220-22	Coppia guide a "C" per griglie GN 2/1				
		74768026	Griglia plastificata GN 2/1				
	EVAP-A		Sovrapprezzo per Vaschetta evaporanda per armadi senza gruppo (modello R)				
	KIT LED 700		Sovrapprezzo per luce LED (solo per GREEN 700 R404a)				
	CONV700		Sovrapprezzo per Kit convogliatore schiena interna				
	KIT RUOTE 700		Sovrapprezzo per KIT 4 RUOTE per armadio 700 lt				
	CONDH2OMKR		Sovrapprezzo per Condensazione ad acqua (Disponibile non prima di 6 settimane)				
	VERS 220-60		Sovrapprezzo Versione 220V/60Hz (macchina non vendibile in Europa)				

* Distanza massima 10 mt ** R = Versione remota *** Moltiplicare per 2 nei modelli doppia temperatura **** Watt TN (-10/+45°C) - Watt BT (-30/+45°C)

PER ALTRI OPTIONAL E ACCESSORI VEDI PG. 86-87

I gas fluorurati a effetto serra sono contenuti in apparecchiature ermeticamente sigillate.

Dati tecnici e caratteristiche soggetti a cambiamento senza preavviso.



Armadi Refrigerati 700 porta cieca, GN2/1, acciaio inox AISI 304 interno ed esterno, con refrigerante naturale R290 o gas R404a (GWP3780)


- Range di temperatura: TN -2°/+7° o BT -24°/-10°
- Accessori di serie: 3 griglie GN2/1 (versione porta intera), 2 griglie GN2/1 (versione 2 mezze porte)
- Ventilatori a basso consumo energetico (mod. R290)
- Isolamento fianchi 70 mm, porta 75 mm. Maxi isolamento fondo, tetto e schiena di 80 mm
- Sbrinamento ed evaporazione acqua di condensa automatici (solo incorporati)
- Guarnizioni ad alta tenuta
- Arresto dei ventilatori durante l'apertura delle porte
- Serratura
- Luce LED standard per i modelli Green Plus (optional per i Green)

Refrigerated cabinets 700 full door, GN2/1, AISI 304 stainless steel interior and exterior, with natural refrigerant R290 or R404a (GWP3780)

- Temperature range: TN -2°/+7° or BT -24°/-10°
- Standard fitting: 3 shelves GN2/1 (1 door version), 2 shelves GN2/1 (2 half door version)
- Low energy consumption fans (mod. R290)
- Sidewall Insulation 70 mm, door 75 mm. Top, bottom and back 80 mm maxi insulation
- Automatic defrosting and water evaporation system (only models with built-in unit)
- High-sealing gaskets
- Fans stopping with open doors
- Lock
- LED Lighting standard for Green Plus models (optional for Green models)



74703220-22



74768026



EVAP-A



KIT LED 700



CONV700



KIT RUOTE 700



CONDH20MKR



220 - 60Hz



Griglie n° Shelves n°	Dimensioni (mm) Dimensions (mm)	Assorbimento / Absorbed power		Voltaggio / Voltage V/Hz	Dimensioni imballo (mm) Packing dimensions (mm)	Peso Netto/Lordo (Kg) Net/Gross weight (kg)	Tempi di consegna Delivery time
		Watt****	Ampere				
3 GN2/1	733x843x2090	247	5.03	230/50	763x873x2170	142 (157)	
3 GN2/1	733x843x2090	275	5.22	230/50	763x873x2170	142 (157)	
3 GN2/1	733x843x2090	275	5.22	230/50	763x873x2170	125 (138)	
						18 (21)	
3 GN2/1	733x843x2090	568	8.52	230/50	763x873x2170	145 (163)	
3 GN2/1	733x843x2090	634	9.15	230/50	763x873x2170	145 (163)	
3 GN2/1	733x843x2090	634	9.15	230/50	763x873x2170	127 (143)	
						31 (34)	
2 GN2/1	733x843x2090	247	5.03	230/50	763x873x2170	142 (157)	
2 GN2/1	733x843x2090	275	5.22	230/50	763x873x2170	142 (157)	
2 GN2/1	733x843x2090	275	5.22	230/50	763x873x2170	125 (138)	
						18 (21)	
2 GN2/1	733x843x2090	568	8.52	230/50	763x873x2170	145 (163)	
2 GN2/1	733x843x2090	634	9.15	230/50	763x873x2170	145 (163)	
2 GN2/1	733x843x2090	634	9.15	230/50	763x873x2170	127 (143)	
						31 (34)	
2 GN2/1	733x873x2090	229 + 229	4.82 + 4.82	230/50	763x873x2170	183 (193)	
2 GN2/1	733x873x2090	229 + 229	4.82 + 4.82	230/50	763x873x2170	146 (154)	
						16 (19)x2	
2 GN2/1	733x873x2090	477 + 477	7.70 + 7.70	230/50	763x873x2170	187 (197)	
2 GN2/1	733x873x2090	477 + 477	7.70 + 7.70	230/50	763x873x2170	149 (157)	
						24 (27)x2	
2 GN2/1	733x873x2090	229 + 477	4.82 + 7.70	230/50	763x873x2170	185 (195)	
2 GN2/1	733x873x2090	229 + 477	4.82 + 7.70	230/50	763x873x2170	148 (156)	
						16 (19)	
						24 (27)	

S/s pair of runners for GN 2/1 shelf

Plastic coated GN 2/1 shelf

Price increase for Water evaporation bowl for cabinets without condensing unit (R model)

Price increase for LED lighting (only for GREEN 700 R404a)

Price increase for Air conveyor kit for 700 lt (ONLY FOR VERS. 700 LT 1 TEMP.)

Price increase for 4 castors (700lbs upright cabinet)

Price increase for Water condensing unit (Available not earlier than 6 weeks)

Price increase Power supply 220V/60Hz (machinery not to be sold in Europe)

*Max distance 10 mt ** R = Remote Version *** To be multiplied by 2 for double temperature models **** Watt TN (-10/+45°C) - Watt BT (-30/+45°C)

FOR OTHER OPTIONS & ACCESSORIES PLEASE SEE PP. 86-87

Fluorinated greenhouse refrigerant gases are contained in hermetically sealed equipment.

All specifications are subject to change without notice.

Disponibile non prima di 5 settimane
Available not earlier than 5 weeks