




TRK

602/3/4R

	Modello <i>Model</i>	Codice <i>Code</i>	Piano <i>Worktop</i>	Unità Condensatrice <i>Condensing Unit</i>
	TRK602RTN	9TRK62RPVA001	con piano <i>with work top</i>	No
	TRK602RTN/A	9TRK62RPLA001	con piano con alzatina <i>with work top with splashback</i>	No
	TRK602RTN/S	9TRK62RPNA001	senza piano <i>without work top</i>	No
	UCTN1-T*	74861750	Unità Condensatrice R404a	
	TRK603RTN	9TRK63RPVA001	con piano <i>with work top</i>	No
	TRK603RTN/A	9TRK63RPLA001	con piano con alzatina <i>with work top with splashback</i>	No
	TRK603RTN/S	9TRK63RPNA001	senza piano <i>without work top</i>	No
	UCTN2-T*	74861752	Unità condensatrice R404a	
	TRK604RTN	9TRK64RPVA001	con piano <i>with work top</i>	No
	TRK604RTN/A	9TRK64RPLA001	con piano con alzatina <i>with work top with splashback</i>	No
	TRK604RTN/S	9TRK64RPNA001	senza piano <i>without work top</i>	No
	UCTN3-T*	74861754	Unità condensatrice R404a	
		74768132	Griglia plastificata 430X325	
		74701947_P600 x2	Coppia guide inox	
	VERS220-60		Sovrapprezzo per Versione 220V/60Hz	
	SOVVCAS1/2		Sovrapprezzo per cassettera 2 cassetti 1/2	
	SOVCAS1/3		Sovrapprezzo per cassettera 3 cassetti 1/3	
	SOVPOVE***		Sovrapprezzo per porta vetro, con illuminazione	

* Distanza massima 5 m ** R = Versione remota *** Condizioni ambiente di funzionamento: MAX umidità 65% MIN temperatura 25°C

**** Watt TN (-10/+45°C)

I gas fluorurati a effetto serra sono contenuti in apparecchiature ermeticamente sigillate.

Dati tecnici e caratteristiche soggetti a cambiamento senza preavviso.




TRK 602 R, 603 R, 604 R – Tavoli refrigerati 2, 3, 4 porte, senza gruppo incorporato, profondità 600 mm, in acciaio INOX AISI 304.

- Profondità 600 mm
- TN (0/+8°), gas refrigerante R 404A (GWP3780)
- Porte con maniglia incassate in alluminio
- Accessori di serie per porta: 1 griglia 430x325 mm

TRK 602 603 604 – S/s AISI 304 refrigerated counters 2, 3, 4 doors, without unit, depth 600 mm.

- 600 mm depth
- TN (0/+8°), refrigerant gas R 404A (GWP3780)
- Doors with embedded aluminium handles
- Standard fitting per door: 1 grid 430x325 mm

OPTIONALS



74768132



SOVCAS1/2600



SOVCAS1/3600



Range Range	Gas Gas	Dimensioni (mm) Dimensions (mm)	Assorbimento / Absorbed power		Vtaggio / Voltage V/Hz	Dimensioni imballo (mm) Packing dimensions (mm)	Peso Netto/Lordo (Kg) Net/Gross weight (kg)	Tempi di in Delivery line
			Watt****	Ampere				
0/8°C	R404a	1040x600x850	0	0	230/50	1320x750x1100	58/79	Disponibile non prima di 4 settimane Available not earlier than 4 weeks
0/8°C	R404a	1040x600x950	0	0	230/50	1320x750x1100	58/79	
0/8°C	R404a	1040x600x810	0	0	230/50	1320x750x1100	58/79	
<i>Condensing unit R404a</i>								
0/8°C	R404a	1500x600x850	0	0	230/50	1760x750x1100	85/112	Disponibile non prima di 4 settimane Available not earlier than 4 weeks
0/8°C	R404a	1500x600x950	0	0	230/50	1760x750x1100	85/112	
0/8°C	R404a	1500x600x810	0	0	230/50	1760x750x1100	85/112	
<i>Condensing unit R404a</i>								
0/8°C	R404a	1960x600x850	0	0	230/50	2250x750x1100	100/132	Disponibile non prima di 4 settimane Available not earlier than 4 weeks
0/8°C	R404a	1960x600x950	0	0	230/50	2250x750x1100	100/132	
0/8°C	R404a	1960x600x810	0	0	230/50	2250x750x1100	100/132	

Condensing unit R404a

Plastic coated 430X325 shelf

S/s pairs of runners (450mm)

Price Increase for Power supply 220V/60Hz

Price increase for Block of 2 x 1/2 drawers

Price increase for Block of 3 x 1/3 drawers

Price increase for glass door with light

* Max distance 5 m ** R = Remote Version *** Environment conditions: 65% MAX humidity, 25 °C MIN temperature

**** Watt TN (-10/+45°C)

Fluorinated greenhouse refrigerant gases are contained in hermetically sealed equipment.

All specifications are subject to change without notice.