

# » Back Bars 900 mm. height



### BA10H-I

- Interior LED light
- Fan assisted cooling
- Double glazed door
- 2 Adjustable shelves
- Adjustable feet



161 112 96 96

Option:



BA-ALU Models with aluminium door frames,  
BA-S/A Models with stainless steel body  
and aluminium door frame



BA-HSD Models with solid doors



All Models available with mirror  
polished stainless steel interior



**Overall features:**

- lamella evaporator (fast pulldown)
- forced in/out airflow in plinth
- closed backside
- IP65 certified controller
- possibility for very cold regulation



**BA20H-I**

- Interior LED light
- Fan assisted cooling
- Double glazed doors
- 4 Adjustable shelves
- Adjustable feet



240 188 156 156



**BA30H-P**

- Interior LED light
- Fan assisted cooling
- 3 Double glazed doors
- 2 Adjustable shelves behind each door
- Adjustable feet



380 266 218 218

## Technical specifications

Model	BA10H-I	BA20H-I	BA30H-P
Climate Class	4	4	4
Temperature Range, °C	2 to 10	2 to 10	2 to 10
Gross Volume, l	124	196	328
Net Volume, l	118	188	320
Cans, 330 ml	161	240	380
Cans, 500 ml	112	188	266
Bottles, 330 ml	96	156	218
Bottles, 0,5 l PET	96	156	218
External Dimensions, WxDxH, mm	600x520x900	900x520x900	1355x520x900
Internal Dimensions, WxDxH, mm	508x355x732	805x345x730	1257x345x730
Doors	1 hinged glass	2 hinged glass	3 hinged glass
Shelves/Baskets	2, 496x350	4, 330x395	6, 405x365
Outer Body	Black	Black	Black
Interior	Stucco Aluminium	Stucco Aluminium	Stucco Aluminium
Castors/Feet	4 adjustable feet	4 adjustable feet	4 adjustable feet
Lock	Y	Y	Y
Voltage/Frequency, V/Hz	220-240/50	220-240/50	220-240/50
Input Power, W	150	175	320
Energy Consumption, kWh/24h			
Gross Weight, kg	49	67,4	94,6
Net Weight, kg	47	65,4	91,6
Noise Level dbA	45	45	45
Type of Cooling	Fan assisted	Fan assisted	Fan assisted
Type of Defrost	Automatic	Automatic	Automatic
Controller	Electronic	Electronic	Electronic
Thermometer	Y	Y	Y
Refrigerant	R600a	R600a	R290
Charge, g	60	70	90
Internal Light	LED	LED	LED