

Disponible acabados de la carta NCS o RAL, incluidos en el precio estándar, excepto alto brillo y metalizados.

VSS-6-6-RGB
VSS-6-9-RGB
VSS-6-13-RGB
VSS-6-16-RGB
VSSB-6-6-RGB
VSSB-6-9-RGB
VSSB-6-13-RGB
VSSB-6-16-RGB

VSS-6-6-RGM
VSS-6-9-RGM
VSS-6-13-RGM
VSS-6-16-RGM
VSS-6-6-RGM
VSS-6-9-RGM
VSS-6-13-RGM
VSS-6-16-RGM

VSS-6-6-RG
VSS-6-9-RG
VSS-6-13-RG
VSS-6-16-RG
VSSB-6-6-RG
VSSB-6-9-RG
VSSB-6-13-RG
VSSB-6-16-RG

Available finish included in NCS or RAL color chart, at the same price, except glossy and metallic finishing

mod.	largo length (mm)	fondo depth (mm)	alto height (mm)	exposición display (m ²)	puertas corredera sliding doors (uds)	puertas abatibles hinged doors (uds)	potencia frig. frig. power (W)	consumo consumption (W)	refrigerante refrigerant
VSS-6-6-RGB	580	710	1100	0,45	0	1	817	1067	R-452A
VSS-6-9-RGB	930	710	1100	0,77	2	0	1096	1376	R-452A
VSS-6-13-RGB	1280	710	1100	1,08	2	0	1096	1739	R-452A
VSS-6-16-RGB	1630	710	1100	1,4	2	0	1497	1963	R-452A
VSS-6-6-RGM	580	710	1195	0,5	0	1	817	1067	R-452A
VSS-6-9-RGM	930	710	1195	0,85	2	0	1096	1376	R-452A
VSS-6-13-RGM	1280	710	1195	1,2	2	0	1096	1739	R-452A
VSS-6-16-RGM	1630	710	1195	1,55	2	0	1497	1963	R-452A
VSS-6-6-RG	580	710	1380	0,54	0	1	817	1067	R-452A
VSS-6-9-RG	930	710	1380	0,9	2	0	1096	1376	R-452A
VSS-6-13-RG	1280	710	1380	1,26	2	0	1096	1739	R-452A
VSS-6-16-RG	1630	710	1380	1,62	2	0	1497	1963	R-452A

MULTIDECK DISPLAY • VITRINAS MURALES

Características técnicas y constructivas sujetas a variación sin previo aviso


VSS-vitrina refrigerada para snack (+2°+8°)

VSSB-vitrina refrigerada para chocolates (+14°+17°, 55% HR)


- Exterior fabricado en chapa de acero plastificada, lacada o inox
- Costados en cristal doble templado, máxima visibilidad
- Interior en acero inoxidable AISI-304 18/10.
- **Cristal doble templado:** costados, frente, encimera y puertas
- Perfiles en aluminio anodizado
- Estantes y encimera de cristal, con iluminación LED 6500 K
- Opción LED 3000 K (luz cálida) o ROSA, al mismo precio
- Aislamiento de poliuretano inyectado, densidad 40 Kg/m³, cero efectos ODP y GWP
- Evaporador ventilado
- Descarche automático con evaporación automática
- Condensación ventilada
- Control electrónico de temperatura
- Indicador de temperatura
- Clase climática 3 (25°C 60%) régimen M1

Todos los modelos se pueden personalizar en decoración
Cualquier decoración incluida en el precio, excepto alto brillo y metalizados

230v 60Hz / 115v 60Hz consultar - consult



VSS
+2°C +8°C



VSSB
+14°C 17°C
55% HR

We reserve the right to change specifications without prior notice


VSS- snacks refrigerated (+2°+8°)

VSSB- chocolate refrigerated (+14°+17°, 55% HR)

- External finish in plastic coated steel, lacquered or stainless steel
- Double glazed sides, max visibility
- Internal finish in AISI-304 18/10 stainless steel
- **Tempered double glazed:** sides, front, top and doors
- Anodised aluminium profiles
- Glass top and shelves, with 6500 K LED lighting
- Optional 3000 K LED (soft light) or PINK, same price
- 40 Kg/m³ density polyurethane insulation, zero ODP and GWP
- Ventilated evaporator
- Auto defrost and automatic evaporation
- Ventilated condensation
- Electronic temperature controller
- External thermometer
- Climate class 3 (25°C 60%) regime M1

All models can be customized in decoration

All decorations are included on price, except glossy or metallic finishing



all photos must be considered as a reference - fotografías no contractuales



VSS-6-9-RG



VSS-6-9-RGB



VSS-6-9-RGM