

KBA


ACCAVALLATI
OVERLAPPING
CHEVAUCHÉS
ÜBERLAPPENDE
SOBREPUESTOS

08 TN E M
09 TN E M

	KBA 08 TN E M	KBA 09 TN E M	Modello	Model	Modèle	Modell	Modelo	
°C	+5 ÷ -2	+5 ÷ -2	Campo applicazione	Application field	Champe d'application	Anwendungsbereich	Campo d'applicación	
	230V/1/50Hz	230V/1/50Hz	Alimentazione	Power supply	Alimentation	Netzanschluß	Alimentación	
A	4,2	4,2	Corrente max. assorbita	Max. absorbed current	Courant absorbé max.	Max. absorbierter Strom	Corriente máx. absorbida	
kW	0,8	0,8	Potenza max. assorbita	Max. absorbed power	Puissance max. absorbée	Max. aufgenommene Leistung	Máx. potencia absorbida	
	R452A	R452A	Tipo refrigerante	Refrigerant type	Tipe du gaz	Kältemittel	Tipo refrigerante	
W	761	761	Resa *	Capacity *	Puissance *	Leistung *	Rendimiento *	
CMP	CV	0.4	Potenza nominale	Power rating	Puissance nominale	Nennleistung	Potencia nominal	
		E	Tipo compressore	Compressor type	Type compresseur	Kompressortyp	Tipo compresor	
CND	mm	3	Passo alette	Fin spacing	Ecart alettes	Lamellenabstand	Paso aletas	
		1 x Ø 230	Ventilatori	Fan	Ventilateur	Ventilator	Ventiladores	
	W	40	Pot. nom. assorbita	Nom. power cons.	Puiss. nom. absorbée	Nennleistungsaufnahme	Pot. nominal absorbida	
	m ³ /h	550	Portata aria	Air volume	Debit d' air	Volumenstrom	Caudal aire	
EVP	mm	4.2	Passo alette	Fin spacing	Ecart alettes	Lamellenabstand	Paso aletas	
		HG	Sbrinamento	Defrost	Dégivrage	Abtauung	Descongelación	
		C	Espansione	Expansion	Expansion	Expansion	Expansión	
		1 x Ø 230	Ventilatori	Fan	Ventilateur	Ventilator	Ventiladores	
	W	40	Pot. nom. assorbita	Nom. power cons.	Puiss. nom. absorbée	Nennleistungsaufnahme	Pot. nominal absorbida	
		m ³ /h	600	Portata aria	Air volume	Debit d' air	Volumenstrom	Caudal aire
	m	2	Freccia d' aria	Air throw	Projection d'air	Reichweite	Flecha de aire	
kg	34	34	Peso netto	Net Weight	Poids net	Nettogewicht	Peso neto	
kg	47	47	Peso lordo	Gross weight	Poids brut	Bruttogewicht	Peso bruto	
	111102151	-	Codice	Code	Code	Kodex	Codigo	


*= -10°C / +40°C TN

mm	800	X	Imballi Packing
mm	390	Y	Emballage Verpackung
mm	800	Z	Embalajes



C : Capillare / Capillary / Capillaire / Kapillar / Capilar
 CMP: Compressore / Compressor / Compresseur / Kompressorleistung / Compresor
 CND: Condensatore / Condenser / Condenseur / Verflüssiger / Condensador
 E : Ermetico / Hermetic / Hermetique / Vollhermetisch / Hermético
 EVP: Evaporatore / Evaporateur / Evaporateur / Verdampfer / Evaporador
 HG : Gas caldo / Hot gas / Gaz chaud / Heissgas / Gas caliente
 P : Potenza frigorifera / Cooling capacity / Puissances frigorifiques / Kälteleistung
 Potencia frigorífica

S : Semiermetico / Semihermetic / Semi-hermetique / Halbhermetisch / Semihermético
 Ta : Temperatura ambiente / Ambient temperature / Température ambiante
 Umgebungstemperatur / Temperatura ambiente
 Tc : Temperatura cella / Cold room temperature / Température chambre froid
 Kühlraumtemperatur / Temperatura cámara
 V : Volume cella / Coldroom volume / Volume chambre / Kühlzellenvolumen / Volumen cámara
 VT : Valvola termostatica / Expansion valve / Détendeur thermostatique / Thermostatisches
 Expansionsventil / Válvula termostática



KBA

RESA - CAPACITY - PUISSANCE - LEISTUNG - RENDIMIENTO / VOLUME - VOLUME - VOLUME - VOLUMEN - VOLUMEN

	Tc [°C]	-2				0				5			
		Ta [°C]	27	32	38	43	27	32	38	43	27	32	38
KBA08 TN E M	P [W]	685	643	596	547	722	691	627	584	845	790	734	679
	V [m3]	3.31	2.61	1.92	1.40	4.09	3.30	2.33	1.75	7.64	5.78	4.14	2.99
KBA09 TN E M	P [W]	730	678	627	575	782	733	676	619	910	862	780	714
	V [m3]	3.66	2.85	2.10	1.55	4.65	3.64	2.64	1.91	8.49	6.64	4.57	3.25