

KBF


SERIE A TAMPONE
SLOT-IN SERIES
SÉRIE À TAMPON
PUFFERSERIE
SERIE DE TAMPÓN

11 TN E M
14 TN E M
17 TN E M

	KBF 11 TN E M	KBF 14 TN E M	KBF 17 TN E M	Modello	Model	Modèle	Modell	Modelo		
°C	+5 ÷ -2	+5 ÷ -2	+5 ÷ -2	Campo applicazione	Application field	Champe d'application	Anwendungsbereich	Campo d'applicación		
	230V/1/50Hz	230V/1/50Hz	230V/1/50Hz	Alimentazione	Power supply	Alimentation	Netzanschluß	Alimentación		
A	6,6	8,1	7,1	Corrente max. assorbita	Max. absorbed current	Courant absorbé max.	Max. absorbierter Strom	Corriente máx. absorbida		
kW	1,2	1,4	1,3	Potenza max. assorbita	Max. absorbed power	Puissance max. absorbée	Max. aufgenommene Leistung	Máx. potencia absorbida		
	R452A	R452A	R452A	Tipo refrigerante	Refrigerant type	Tipe du gaz	Kältemittel	Tipo refrigerante		
W	1032	1204	1421	Resa *	Capacity *	Puissance *	Leistung *	Rendimiento *		
CMP	CV	0.5	0.75	1	Potenza nominale	Power rating	Puissance nominale	Nennleistung	Potencia nominal	
		E	E	E	Tipo compressore	Compressor type	Type compresseur	Kompressortyp	Tipo compresor	
CND	mm	2.5	2.5	2.5	Passo alette	Fin spacing	Ecart alettes	Lamellenabstand	Paso aletas	
		1 x Ø 254	1 x Ø 254	1 x Ø 254	Ventilatori	Fan	Ventilateur	Ventilator	Ventiladores	
	W	73	73	73	Pot. nom. assorbita	Nom. power cons.	Puiss. nom. absorbée	Nennleistungsaufnahme	Pot. nominal absorbida	
	m ³ /h	750	750	750	Portata aria	Air volume	Debit d' air	Volumenstrom	Caudal aire	
EVP	mm	4.2	4.2	4.2	Passo alette	Fin spacing	Ecart alettes	Lamellenabstand	Paso aletas	
		HG	HG	HG	Sbrinamento	Defrost	Dégivrage	Abtauung	Descongelación	
		C	C	C	Espansione	Expansion	Expansion	Expansion	Expansión	
		1 x Ø 254	1 x Ø 254	1 x Ø 254	Ventilatori	Fan	Ventilateur	Ventilator	Ventiladores	
	W	73	73	73	Pot. nom. assorbita	Nom. power cons.	Puiss. nom. absorbée	Nennleistungsaufnahme	Pot. nominal absorbida	
		m ³ /h	700	700	700	Portata aria	Air volume	Debit d' air	Volumenstrom	Caudal aire
	m	3	3	3	Freccia d' aria	Air throw	Projection d'air	Reichweite	Flecha de aire	
kg	58	60	64	Peso netto	Net Weight	Poids net	Nettogewicht	Peso neto		
kg	81	83	87	Peso lordo	Gross weight	Poids brut	Bruttogewicht	Peso bruto		
	111102351	111102352	111102353	Codice	Code	Code	Kodex	Codigo		


*= -10°C / +40°C TN

mm	520	X	Imballi Packing
mm	1020	Y	Emballage Verpackung
mm	930	Z	Embalajes



C : Capillare / Capillary / Capillaire / Kapillar / Capilar
 CMP: Compressore / Compressor / Compresseur / Kompressorleistung / Compresor
 CND: Condensatore / Condenser / Condenseur / Verflüssiger / Condensador
 E : Ermetico / Hermetic / Hermetique / Vollhermetisch / Hermético
 EVP: Evaporatore / Evaporateur / Evaporateur / Verdampfer / Evaporador
 HG : Gas caldo / Hot gas / Gaz chaud / Heissgas / Gas caliente
 P : Potenza frigorifera / Cooling capacity / Puissances frigorifiques / Kälteleistung
 Potencia frigorífica

S : Semiermetico / Semihermetic / Semi-hermetique / Halbhermetisch / Semierhmetico
 Ta : Temperatura ambiente / Ambient temperature / Température ambiente
 Umgebungstemperatur / Temperatura ambiente
 Tc : Temperatura cella / Cold room temperature / Température chambre froid
 Kühlraumtemperatur / Temperatura cámara
 V : Volume cella / Coldroom volume / Volume chambre / Kühlzellenvolumen / Volumen cámara
 VT : Valvola termostatica / Expansion valve / Détendeur thermostatique / Thermostatisches
 Expansionsventil / Válvula termostática



KBF

Serie a tampon - Slot-in series - Série á tampon - Pufferserie - Serie de tampon

RESA - CAPACITY - PUISSANCE - LEISTUNG - RENDIMIENTO / VOLUME - VOLUME - VOLUME - VOLUMEN - VOLUMEN

	Tc [°C]	-2				0				5			
		Ta [°C]	27	32	38	43	27	32	38	43	27	32	38
KBF 11 TN E M	P [W]	981	915	825	766	1054	983	901	823	1212	1132	1035	947
	V [m3]	5.83	4.61	3.30	2.51	7.36	5.81	4.25	3.11	13.30	10.21	7.24	5.22
KBF 14 TN E M	P [W]	1154	1090	975	895	1237	1149	1073	1006	1434	1364	1294	1242
	V [m3]	7.48	6.03	4.33	3.24	9.45	7.41	5.62	4.33	17.07	13.57	10.30	8.12
KBF 17 TN E M	P [W]	1266	1155	1072	971	1330	1260	1145	1071	1566	1490	1413	1360
	V [m3]	8.62	6.64	5.04	3.72	10.50	8.55	6.23	4.81	19.47	15.53	11.85	9.39