


# KS

**13 TN E M**
**17 TN E M**

	KS 13 TN E M	KS 17 TN E M	Modello	Model	Modèle	Modell	Modelo
°C	+5 ÷ -2°C	+5 ÷ -2°C	Campo applicazione	Application field	Champe d'application	Anwendungsbereich	Campo d'aplicación
	230V/1/50Hz	230V/1/50Hz	Alimentazione	Power supply	Alimentation	Netzanschluß	Alimentación
A	8,7	7,6	Corrente max. assorbita	Max. absorbed current	Courant absorbé max.	Max. absorbierter Strom	Corriente máx. absorbida
kW	1,5	1,4	Potenza max. assorbita	Max. absorbed power	Puissance max. absorbée	Max. aufgenommene Leistung	Máx. potencia absorbida
	R404A/R507/ R452A	R404A/R507/ R452A	Tipo refrigerante	Refrigerant type	Tipe du gaz	Kältemittel	Tipo refrigerante
W	1204	1421	Resa *	Capacity *	Puissance *	Leistung *	Rendimiento *
CMP	W	1,5	Pot. nom. assorbita	Nom. power cons.	Puiss. nom. absorbée	Nennleistungsaufnahme	Pot. nominal absorbida
	CV	0,75	Potenza nominale	Power rating	Puissance nominale	Nennleistung	Potencia nominal
		E	Tipo compressore	Compressor type	Type compresseur	Kompressortyp	Tipo compresor
CND	mm	2,5	Passo alette	Fin spacing	Ecart alettes	Lamellenabstand	Paso aletas
		1 x Ø254	Ventilatori	Fan	Ventilateur	Ventilator	Ventiladores
	W	95	Pot. nom. assorbita	Nom. power cons.	Puiss. nom. absorbée	Nennleistungsaufnahme	Pot. nominal absorbida
	m <sup>3</sup> /h	700	Portata aria	Air volume	Debit d' air	Volumenstrom	Caudal aire
EVP	mm	4,2 ÷ 8,4	Passo alette	Fin spacing	Ecart alettes	Lamellenabstand	Paso aletas
		EL	Sbrinamento	Defrost	Dégivrage	Abtauung	Descongelación
		VT	Espansione	Expansion	Expansion	Expansion	Expansión
		2 x Ø254	Ventilatori	Fan	Ventilateur	Ventilator	Ventiladores
	W	146	Pot. nom. assorbita	Nom. power cons.	Puiss. nom. absorbée	Nennleistungsaufnahme	Pot. nominal absorbida
	m <sup>3</sup> /h	1300	Portata aria	Air volume	Debit d' air	Volumenstrom	Caudal aire
	m	9	Freccia d' aria	Air throw	Projection d'air	Reichweite	Flecha de aire
kg	62	64	Peso netto	Net Weight	Poids net	Nettogewicht	Peso neto
kg	89	91	Peso lordo	Gross weight	Poids brut	Bruttogewicht	Peso bruto
	111103503	111103504	Codice	Code	Code	Kodex	Codigo




\* = -10°C / +40°C TN

KS		EVAPORATORE		
1260	X	-	X	Imballi Packing
600	Y	-	Y	Emballage Verpackung
875	Z	-	Z	Embalajes



C : Capillare / Capillary / Capillaire / Kapillar / Capilar  
 CMP: Compressore / Compressor / Compresseur / Kompressorleistung / Compresor  
 CND: Condensatore / Condenser / Condenseur / Verflüssiger / Condensador  
 E : Ermetico / Hermetic / Hermétique / Vollhermetisch / Hermético  
 EVP: Evaporatore / Evaporateur / Evaporateur / Verdampfer / Evaporador  
 HG : Gas caldo / Hot gas / Gaz chaud / Heissgas / Gas caliente  
 P : Potenza frigorifera / Cooling capacity / Puissances frigorifiques / Kälteleistung  
 Potenza frigorifica

S : Semiermetico / Semihermetic / Semi-hermetique / Halbhermetisch / Semihermético  
 Ta : Temperatura ambiente / Ambient temperature / Température ambiente  
 Umgebungstemperatur / Temperatura ambiente  
 Tc : Temperatura cella / Cold room temperature / Température chambre froid  
 Kühlraumtemperatur / Temperatura cámara  
 V : Volume cella / Coldroom volume / Volume chambre / Kühlzellenvolumen / Volumen cámara  
 VT : Valvola termostatica / Expansion valve / Détendeur thermostatique / Thermostatisches  
 Expansionsventil / Válvula termostática



RESA - CAPACITY - PUISSANCE - LEISTUNG - RENDIMIENTO / VOLUME - VOLUME - VOLUME - VOLUMEN - VOLUMEN

	Tc [°C]	-2				0				5			
		Ta [°C]	27	32	38	43	27	32	38	43	27	32	38
KS 13 TN E M	P [W]	1323	1235	1144	1086	1400	1337	1250	1204	1641	1571	1523	1498
	V [m3]	9.10	7.03	5.60	4.00	11.50	9.41	7.23	5.83	20.90	16.90	13.30	10.70
KS 17 TN E M	P [W]	1465	1372	1276	1159	1566	1490	1413	1311	1833	1789	1700	1682
	V [m3]	13.62	8.64	7.04	5.72	14.50	10.55	9.23	7.81	23.40	18.53	16.85	12.39