


KS

20 TN E M
20 TN E T

	KS 20 TN E M	KS 20 TN E T	Modello	Model	Modèle	Modell	Modelo
°C	+5 ÷ -2°C	+5 ÷ -2°C	Campo applicazione	Application field	Champe d'application	Anwendungsbereich	Campo d'aplicación
	230V/1/50Hz	400V/3/50Hz	Alimentazione	Power supply	Alimentation	Netzanschluß	Alimentación
A	8,1	4,8	Corrente max. assorbita	Max. absorbed current	Courant absorbé max.	Max. absorbierter Strom	Corriente máx. absorbida
kW	1,7	1,8	Potenza max. assorbita	Max. absorbed power	Puissance max. absorbée	Max. aufgenommene Leistung	Máx. potencia absorbida
	R404A/R507/ R452A	R404A/R507/ R452A	Tipo refrigerante	Refrigerant type	Tipe du gaz	Kältemittel	Tipo refrigerante
W	1800	1868	Resa *	Capacity *	Puissance *	Leistung *	Rendimiento *
CMP	W	1,97	Pot. nom. assorbita	Nom. power cons.	Puiss. nom. absorbée	Nennleistungsaufnahme	Pot. nominal absorbida
	CV	1,0	Potenza nominale	Power rating	Puissance nominale	Nennleistung	Potencia nominal
		E	Tipo compressore	Compressor type	Type compresseur	Kompressortyp	Tipo compresor
CND	mm	2,5	Passo alette	Fin spacing	Ecart alettes	Lamellenabstand	Paso aletas
		2 x Ø254	Ventilatori	Fan	Ventilateur	Ventilator	Ventiladores
	W	190	Pot. nom. assorbita	Nom. power cons.	Puiss. nom. absorbée	Nennleistungsaufnahme	Pot. nominal absorbida
	m ³ /h	1400	Portata aria	Air volume	Debit d' air	Volumenstrom	Caudal aire
EVP	mm	4,2 ÷ 8,4	Passo alette	Fin spacing	Ecart alettes	Lamellenabstand	Paso aletas
		EL	Sbrinamento	Defrost	Dégivrage	Abtauung	Descongelación
		VT	Espansione	Expansion	Expansion	Expansion	Expansión
		2 x Ø254	Ventilatori	Fan	Ventilateur	Ventilator	Ventiladores
	W	146	Pot. nom. assorbita	Nom. power cons.	Puiss. nom. absorbée	Nennleistungsaufnahme	Pot. nominal absorbida
		m ³ /h	1300	Portata aria	Air volume	Debit d' air	Volumenstrom
	m	9	Freccia d' aria	Air throw	Projection d'air	Reichweite	Flecha de aire
kg	85	85	Peso netto	Net Weight	Poids net	Nettogewicht	Peso neto
kg	118	118	Peso lordo	Gross weight	Poids brut	Bruttogewicht	Peso bruto
	111103505	111103597	Codice	Code	Code	Kodex	Codigo




* = -10°C / +40°C TN

KS		EVAPORATORE		
1452	X	-	X	Imballi Packing
632	Y	-	Y	Emballage Verpackung
906	Z	-	Z	Embalajes



C : Capillare / Capillary / Capillaire / Kapillar / Capilar
 CMP: Compressore / Compressor / Compresseur / Kompressorleistung / Compresor
 CND: Condensatore / Condenser / Condenseur / Verflüssiger / Condensador
 E : Ermetico / Hermetic / Hermétique / Vollhermetisch / Hermético
 EVP: Evaporatore / Evaporateur / Evaporateur / Verdampfer / Evaporador
 HG : Gas caldo / Hot gas / Gaz chaud / Heissgas / Gas caliente
 P : Potenza frigorifera / Cooling capacity / Puissances frigorifiques / Kälteleistung
 Potenza frigorifica

S : Semiermetico / Semihermetic / Semi-hermetique / Halbhermetisch / Semihermético
 Ta : Temperatura ambiente / Ambient temperature / Température ambiente
 Umgebungstemperatur / Temperatura ambiente
 Tc : Temperatura cella / Cold room temperature / Température chambre froid
 Kühlraumtemperatur / Temperatura cámara
 V : Volume cella / Coldroom volume / Volume chambre / Kühlzellenvolumen / Volumen cámara
 VT : Valvola termostatica / Expansion valve / Détendeur thermostatique / Thermostatisches
 Expansionsventil / Válvula termostática



RESA - CAPACITY - PUISSANCE - LEISTUNG - RENDIMIENTO / VOLUME - VOLUME - VOLUME - VOLUMEN - VOLUMEN

	Tc [°C]	-2				0				5			
		Ta [°C]	27	32	38	43	27	32	38	43	27	32	38
KS 20 TN E M	P [W]	1953	1807	1655	1553	2083	1956	1825	1724	2390	2309	2214	2100
	V [m3]	16.48	13.14	9.94	7.87	20.51	16.63	12.88	10.22	36.10	29.90	23.62	18.50
KS 20 TN E T	P [W]	1945	1833	1707	1573	2113	2026	1846	1701	2517	2360	2145	1972
	V [m3]	16.45	13.40	10.60	8.07	21.12	17.70	13.15	10.01	38.80	31.05	22.89	16.97