



NEW 2020

SPRING PLUS 802

Tavoli refrigerati ventilati su piedi o ruote, profondità 800 mm in acciaio inox AISI 304, 2 vani EN400x600, con 3 coppie guide inox a L per porta.

S/s AISI 304 ventilated refrigerated counters on feet or castors, 800 mm of depth, 2 doors EN400x600 with 3 pairs of L runners per door.

- Gruppo incorporato o remoto
- Piano dritto, con alzatina o senza piano
- Controller elettronico con display digitale 8 tasti
- Fermo porta a 90° e richiamo automatico
- Interni arrotondati
- Evaporatore rialzato (pulizia facilitata).
- Sbrinamento ed evaporazione dell'acqua di condensa automatici (mod. incorporati).

- Built in or remote unit
- Versions with straight worktop, worktop with splashback or without top
- Electronic controller with 8 keys digital display
- 90° stop self-closing doors
- Inner bottom panel with rounded corners
- Raised evaporator (easy cleaning)
- Automatic systems for defrosting and evaporation of the condensation water (only models with built-in unit).

Optional: griglie plastificate o inox, sterilizzatore.

Optional: S/S or plastic coated shelves, sterilizer.




ACCESSORI DI SERIE  
STANDARD ACCESSORIES  
Vano refrigerato EN400x600  
Refrigerated room EN400x600



EVAP-T



KIT 4 RUOTE



220 - 60Hz  
VERS 220-60



OZONIZER  
STERIL KIT\*

Incompatibile con LED\*  
Not compatible with LED\*



Modello Model	Codice Code	Piano Worktop	Range Range	GAS GAS	Classe energetica Energy class	Classe climatica Climate class	Consumo elettrico annuale Annual electricity consumption	Volume utile netto Net storage volume L	Dimensioni Dimensions mm	Assorbimento Absorbed power Watt**** A	Voltaggio Voltage Volt/Ph/Hz	Dimensioni imballo Packing dimensions mm	Peso Netto/Lordo Net/Gross weight Kg
SPRINGPLUS802TN	6ST82IP2VA001	Piano dritto / Straight worktop	-2/+7° C	R290 GWP 3 Kg 0,100	A	5 40°C - 40%HR	448	240	1450x800x850	247	5.03	1510x860x1040	135/153
SPRINGPLUS802TN/A	6ST82IP2LA001	Piano + alzatina / Work top with splashback							1450x800x950	247	5.03	1510x860x1040	136/154
SPRINGPLUS802TN/S	6ST82IP2NA001	Senza piano / Without worktop							1450x790x800	247	5.03	1510x860x1040	96/109
SPRINGPLUS802BT	6ST82IB2VA001	Piano dritto / Straight worktop	-24/-10° C	R290 GWP 3 Kg 0,14	G	5 40°C - 40%HR	4280	240	1450x800x850	526	7.21	1510x860x1040	147/167
SPRING802PLUSBT/A	6ST82IB2LA001	Piano + alzatina / Work top with splashback							1450x800x950	526	7.21	1510x860x1040	148/168
SPRING802PLUSBT/S	6ST82IB2NA001	Senza piano / Without worktop							1450x790x800	526	7.21	1510x860x1040	108/123
SPRING802TN R **	6ST82RP4VA001	Con piano - With work top	-2/+7° C					240	1310x800x850		230/1/50	1510x860x1040	105/119
SPRING802TN/A R **	6ST82RP4LA001	Con piano con alzatina - Work top with splashback							1310x800x950		230/1/50	1510x860x1040	115/131
SPRING802TN/S R **	6ST82RP4NA001	Senza piano - Without work top							1310x790x800		230/1/50	1510x860x1040	77/88
UCTN2-T*	74861752	Unità Condensatrice							350x460x265			350x460x265	25/45
VALVR452A-802TN	74877075	Valvola R452A per modello remoto (fornita smontata) (mod. 802TN)							101x38x77			101x38x77	0,3/0,3
SPRING802BT R **	6ST82RB4VA001	Con piano - With work top	-24/-10° C					240	1310x800x850		230/1/50	1510x860x1040	105/119
SPRING802BT/A R **	6ST82RB4LA001	Con piano con alzatina - Work top with splashback							1310x800x950		230/1/50	1510x860x1040	115/131
SPRING802BT/S R**	6ST82RB4NA001	Senza piano - Without work top							1310x790x800		230/1/50	1510x860x1040	84/95
UCBT2-T*	74861760	Unità Condensatrice							415x540x340			415x540x340	40/60
VALVR452A-802BT	74877089	Valvola R452A per modello remoto (fornita smontata) (mod. 802BT)							101x38x77			101x38x77	0,3/0,3
STERILKIT	73688492	Sovrapprezzo Sterilizzatore											
EVAP-T		Sovrapprezzo per vaschetta evapora condensa per tavoli senza gruppo R											
	74768570	Coppia guide a "L" per vassoi EN 600x400											
	74768122	Griglia plastificata EN 600x400											
	74768120	Griglia inox EN 600x400											
KIT 4 RUOTE		Sovrapprezzo per 4 ruote											
VERS220-60		Sovrapprezzo Versione 220V/60Hz											

\* Distanza massima 10m \*\* R= Versione remota \*\*\* Watt TN (-10/+45°C) - Watt BT (-30/+45°C)

I gas fluorurati a effetto serra sono contenuti in apparecchiature ermeticamente sigillate.

Dati tecnici e caratteristiche soggetti a cambiamento senza preavviso.

\* Max distance 10m \*\* R= Remote Version \*\*\* Watt TN (-10/+45°C) - Watt BT (-30/+45°C)

Fluorinated greenhouse refrigerant gases are contained in hermetically sealed equipment.

All specifications are subject to change without notice.



NEW 2020

SPRING PLUS 803

Tavoli refrigerati ventilati su piedi o ruote, profondità 800 mm in acciaio inox AISI 304, 3 vani EN400x600, con 3 coppie guide inox a L per porta.

S/s AISI 304 ventilated refrigerated counters on feet or castors, 800 mm of depth, 3 doors EN400x600 with 3 pairs of L runners per door.

- Gruppo incorporato o remoto
- Piano dritto, con alzatina o senza piano
- Controller elettronico con display digitale 8 tasti
- Fermo porta a 90° e richiamo automatico
- Interni arrotondati
- Evaporatore rialzato (pulizia facilitata).
- Sbrinamento ed evaporazione dell'acqua di condensa automatici (mod. incorporati).

- Built in or remote unit
- Versions with straight worktop, worktop with splashback or without top
- Electronic controller with 8 keys digital display
- 90° stop self-closing doors
- Inner bottom panel with rounded corners
- Raised evaporator (easy cleaning).
- Automatic systems for defrosting and evaporation of the condensation water (only models with built-in unit).

Optional: griglie plastificate o inox, sterilizzatore.

Optional: S/S or plastic coated shelves, sterilizer.



EVAP-T



KIT 4 RUOTE



VERS 220-60





OZONIZER STERIL KIT\*



ACCESSORI DI SERIE  
STANDARD ACCESSORIES  
Vano refrigerato EN400x600  
Refrigerated room EN400x600

Incompatibile con LED\*  
Not compatible with LED\*



Modello Model	Codice Code	Piano Worktop	Range Range	GAS GAS	Classe energetica Energy class	Classe climatica Climate class	Consumo elettrico annuale Annual electricity consumption	Volume utile netto Net storage volume L	Dimensioni Dimensions	Assorbimento Absorbed power		Voltaggio Voltage Volt/Ph/Hz	Dimensioni imballo Packing dimensions mm	Peso Netto/Lordo Net/Gross weight Kg	
										Watt****	A				
	<b>SPRINGPLUS803TN</b>	6ST83IP2VA001	Piano dritto / Straight worktop												
	<b>SPRINGPLUS803TN/A</b>	6ST83IP2LA001	Piano + alzatina / Work top with splashback	-2/+7° C	R290 GWP 3 Kg 0,100	A	5 40°C - 40%HR	515	360	2004x800x850	247	5.03	230/1/50	2064x860x1040	158/179
	<b>SPRINGPLUS803TN/S</b>	6ST83IP2NA001	Senza piano / Without worktop							2004x800x950	247	5.03	230/1/50	2064x860x1040	161/183
	<b>SPRINGPLUS803TN/S</b>	6ST83IP2NA001	Senza piano / Without worktop							2004x790x800	247	5.03	230/1/50	2064x860x1040	120/136
	<b>SPRINGPLUS803BT</b>	6ST83IB2VA001	Piano dritto / Straight worktop												
	<b>SPRINGPLUS803BT/A</b>	6ST83IB2LA001	Piano + alzatina / Work top with splashback	-24/-10° C	R290 GWP 3 Kg 0,14	G	5 40°C - 40%HR	4922	360	2004x800x850	526	7.21	230/1/50	2064x860x1040	169/192
	<b>SPRINGPLUS803BT/S</b>	6ST83IB2NA001	Senza piano / Without worktop							2004x800x950	526	7.21	230/1/50	2064x860x1040	172/196
	<b>SPRINGPLUS803BT/S</b>	6ST83IB2NA001	Senza piano / Without worktop							2004x790x800	526	7.21	230/1/50	2064x860x1040	131/149
	<b>SPRING803TN R **</b>	6ST83RP4VA001	Con piano - With work top												
	<b>SPRING803TN/A R**</b>	6ST83RP4LA001	Con piano con alzatina - Work top with splashback	-2/+7° C						1864x800x850			230/1/50	2064x860x1040	137/156
	<b>SPRING803TN/S R**</b>	6ST83RP4NA001	Senza piano - Without work top							1864x800x950			230/1/50	2064x860x1040	139/158
	<b>SPRING803TN/S R**</b>	6ST83RP4NA001	Senza piano - Without work top							1864x790x800			230/1/50	2064x860x1040	100/114
	<b>UCTN3-T*</b>	74861754	Unità Condensatrice							350x500x300				350x500x300	33/53
	<b>VALVR452A-803TN</b>	74877077	Valvola R452A per modello remoto (fornita smontata) (mod. 803TN)							101x38x77				101x38x77	0,3/0,3
	<b>SPRING803BT R **</b>	6ST83RB4VA001	Con piano - With work top												
	<b>SPRING803BT/A R**</b>	6ST83RB4LA001	Con piano con alzatina - Work top with splashback	-24/-10° C						1864x800x850			230/1/50	2064x860x1040	137/156
	<b>SPRING803BT/S R **</b>	6ST83RB4NA001	Senza piano - Without work top							1864x800x950			230/1/50	2064x860x1040	139/158
	<b>SPRING803BT/S R **</b>	6ST83RB4NA001	Senza piano - Without work top							1864x790x800			230/1/50	2064x860x1040	100/114
	<b>UCBT3-T*</b>	74861762	Unità Condensatrice							415x540 x340				415x540 x340	40/60
	<b>VALVR452A-803BT</b>	74877089	Valvola R452A per modello remoto (fornita smontata) (mod. 803BT)							101x38x77				101x38x77	0,3/0,3
	<b>STERILKIT</b>	73688492	Sovrapprezzo Sterilizzatore												
	<b>EVAP-T</b>		Sovrapprezzo per vaschetta evapora condensa per tavoli senza gruppo R												
		74768570 x2	Coppia guide a "L" per vassoi EN 600x400												
		74768122	Griglia plastificata EN 600x400												
		74768120	Griglia inox EN 600x400												
	<b>KIT 4 RUOTE</b>		Sovrapprezzo per 4 ruote												
	<b>VERS220-60</b>		Sovrapprezzo Versione 220V/60Hz												

\* Distanza massima 10m \*\* R= Versione remota \*\*\* Watt TN (-10/+45°C) - Watt BT (-30/+45°C)

I gas fluorurati a effetto serra sono contenuti in apparecchiature ermeticamente sigillate.

Dati tecnici e caratteristiche soggetti a cambiamento senza preavviso.

\* Max distance 10m \*\* R= Remote Version \*\*\* Watt TN (-10/+45°C) - Watt BT (-30/+45°C)

Fluorinated greenhouse refrigerant gases are contained in hermetically sealed equipment.

All specifications are subject to change without notice.





**NEW 2020**

# SPRING PLUS 804

## SPRING PLUS



**Tavoli refrigerati ventilati su piedi o ruote, profondità 800 mm in acciaio inox AISI 304, 4 vani EN400x600, con 3 coppie guide inox a L per porta.**

**S/s AISI 304 ventilated refrigerated counters on feet or castors, 800 mm of depth, 4 doors EN400x600 with 3 pairs of L runners per door.**

- Gruppo incorporato o remoto
- Piano dritto, con alzatina o senza piano
- Controller elettronico con display digitale 8 tasti
- Fermo porta a 90° e richiamo automatico
- Interni arrotondati
- Evaporatore rialzato (pulizia facilitata)
- Sbrinamento ed evaporazione dell'acqua di condensa automatici (mod. incorporati)

- Built in or remote unit
- Versions with straight worktop, worktop with splashback or without top
- Electronic controller with 8 keys digital display
- 90° stop self-closing doors. Inner bottom panel with rounded corners
- Raised evaporator (easy cleaning)
- Automatic systems for defrosting and evaporation of the condensation water (only models with built-in unit).

**Optional:** griglie plastificate o inox, sterilizzatore.

**Optional:** S/S or plastic coated shelves, sterilizer.



EVAP-T



KIT 4 RUOTE



VERS 220-60



OZONIZER STERIL KIT\*



**ACCESSORI DI SERIE STANDARD ACCESSORIES**  
Vano refrigerato EN400x600  
Refrigerated room EN400x600

Incompatibile con LED\*  
Not compatible with LED\*



Modello Model	Codice Code	Piano Worktop	Range Range	GAS GAS	Classe energetica Energy class	Classe climatica Climate class	Consumo elettrico annuale Annual electricity consumption	Volume utile netto Net storage volume L	Dimensioni Dimensions mm	Assorbimento Absorbed power		Vantaggio Voltage Volt/Ph/Hz	Dimensioni imballo Packing dimensions mm	Peso Netto/Lordo Net/Gross weight Kg
										Watt****	A			
	<b>SPRINGPLUS804TN</b>	6ST84IP2VA001	Piano dritto / Straight worktop	-2/+7° C	R290 GWP 3 Kg 0,100	A	582	480	2560x800x850	247	5.03	230/1/50	2620x860x1040	199/226
	<b>SPRINGPLUS804TN/A</b>	6ST84IP2LA001	Piano + alzatina / Work top with splashback						2560x800x950	247	5.03	230/1/50	2620x860x1040	199/226
	<b>SPRINGPLUS804TN/S</b>	6ST84IP2NA001	Senza piano / Without worktop						2560x790x800	247	5.03	230/1/50	2620x860x1040	150/170
	<b>SPRINGPLUS804BT</b>	6ST84IB2VA001	Piano dritto / Straight worktop	-24/-10° C	R290 GWP 3 Kg 0,14	D	3740	480	2560x800x850	526	7.21	230/1/50	2620x860x1040	211/240
	<b>SPRINGPLUS804BT/A</b>	6ST84IB2LA001	Piano + alzatina / Work top with splashback						2560x800x950	526	7.21	230/1/50	2620x860x1040	211/240
	<b>SPRINGPLUS804BT/S</b>	6ST84IB2NA001	Senza piano / Without worktop						2560x790x800	526	7.21	230/1/50	2620x860x1040	162/184
	<b>SPRING804TN R**</b>	6ST84RP4VA001	Con piano - With work top	-2/+7° C		5 40°C - 40%HR		480	2420x800x850			230/1/50	2620x860x1040	177/201
	<b>SPRING804TN/A R**</b>	6ST84RP4LA001	Con piano con alzatina - Work top with splashback						2420x800x950			230/1/50	2620x860x1040	178/202
	<b>SPRING804TN/S R**</b>	6ST84RP4NA001	Senza piano - Without work top						2420x790x800			230/1/50	2620x860x1040	130/148
	<b>UCTN4-T*</b>	74861756	Unità Condensatrice	Condensing unit		350x500x300			350x500x300				35/55	
	<b>VALVR452A-804TN</b>	74877077	Valvola R452A per modello remoto (fornita smontata) (mod. 804TN)	R452A Valve for remote model (supplied not installed) (mod. 804TN)		101x38 x77			101x38 x77				0,3/0,3	
	<b>SPRING804BT R**</b>	6ST84RB4VA001	Con piano - With work top	-24/-10° C		5 40°C - 40%HR		480	2420x800x850			230/1/50	2620x860x1040	177/201
<b>SPRING804BT/A R**</b>	6ST84RB4LA001	Con piano con alzatina - Work top with splashback	2420x800x950								230/1/50	2620x860x1040	178/202	
<b>SPRING804BT/S R**</b>	6ST84RB4NA001	Senza piano - Without work top	2420x790x800								230/1/50	2620x860x1040	130/148	
<b>UCBT4-T*</b>	74861764	Unità Condensatrice	Condensing unit		514x540x340			514x540x340				55/75		
<b>VALVR452A-804BT</b>	74877081	Valvola R452A per modello remoto (fornita smontata) (mod. 804BT)	R452A Valve for remote model (supplied not installed) (mod. 804BT)		101x38x77			101x38x77				0,3/0,3		
<b>STERILKIT</b>	73688492	Sovrapprezzo Sterilizzatore	Price increase for Sterilizer											
<b>EVAP-T</b>		Sovrapprezzo per vaschetta evapora condensa per tavoli senza gruppo R	Price Increase for water tray for counters without condensing unit (R model)											
	74768570 x2	Coppia guide a "L" per vassoi EN 600x400	"L" pair of runners for EN 60x40 trays											
	74768122	Griglia plastificata EN 600x400	Plastic coated EN 60x40 shelf											
	74768120	Griglia inox EN 600x400	S/S EN 600x400 shelf											
<b>KIT 6 RUOTE</b>		Sovrapprezzo per 6 ruote	Price increase for 6 castors											
<b>VERS220-60</b>		Sovrapprezzo Versione 220V/60Hz	Price Increase Power supply 220V/60Hz											

\* Distanza massima 10m \*\* R= Versione remota \*\*\* Watt TN (-10/+45°C) - Watt BT (-30/+45°C)

I gas fluorurati a effetto serra sono contenuti in apparecchiature ermeticamente sigillate.

Dati tecnici e caratteristiche soggetti a cambiamento senza preavviso.

\* Max distance 10m \*\* R= Remote Version \*\*\* Watt TN (-10/+45°C) - Watt BT (-30/+45°C)

Fluorinated greenhouse refrigerant gases are contained in hermetically sealed equipment.

All specifications are subject to change without notice.