

| DUO |

PERFECT VIEW



DUO 127

| | DUO 80 | DUO 127 |
|-------------------------------|---|---|
| Climate class | 3 | 3 |
| Ambient temperature range | +10 to +25 | +10 to +25 |
| Gross volume, litres | 123 | 224 |
| Net volume, litres | 82 | 139 |
| Temperature range inside unit | -16 to -23 | -16 to -23 |
| Refrigerants available: | R404a / R290 | R404a / R290 |
| Energy consumption/ 24 h | 9,03 (R290) | 14,62 (R290) |
| Input power (watt) | 447 | 850 |
| DIMENSIONS | | |
| External dim. (WxDxH) | 800*750*1178 | 1270*750*1178 |
| Internal dim. (WxDxH) upper | 670*325*380 | 1140*325*380 |
| Internal dim. (WxDxH) lower | 670*530*440 | 1140*530*440 |
| Insulation (mm) | 60 | 60 |
| ACCESSORIES | | |
| Divider | 2 in top section/ 2 in lower section | 4 in top section/ 4 in lower section |
| Feet | Incl. | Incl. |
| Lock | n / a | n/a |
| Thermometer | Analog | Analog |
| Digital controller | n/a | n/a |
| Internal light | Incl. | Incl. |
| OTHER DATA | | |
| Outer cabinet | White | White |
| Inner cabinet | Painted steel | Painted steel |
| Graphics | Optional | Optional |
| Type of cooling | Static | Static |
| Type of defrost | Manual | Manual |
| Power | 220 v/ 50 Hz | 220 v/ 50 Hz |
| Power 110volt / 60 hz | Optional | Optional |
| Net weight, kg | 83 | 123 |
| Gross weight, kg | 93 | 135 |
| SHIPPING | | |
| 20' cont. Capacity | 12 | 10 |
| 40' cont. Capacity | 28 | 22 |
| 40' cont. HC Capacity | 56 | 44 |
| Standard Trailer capacity | 64 | 52 |

FEATURES

- Low service costs
- Perfect view to the products
- Long life
- Graphics (option)

MINIMUM QUANTITY APPLIES

| MOBILUX |

BATTERY FREEZER W. TRICYCLE

Combi version of freezer and cooler. The Mobilux 12 V freezer or cooler is the right choice if you need mobility or don't have power available. It will help you to sell your ice cream, frozen foods or cold drinks in places, where this normally would not be possible as it can be supplied and installed on a tricycle. It works with an input of 230 volt/ 110 volt to a charger, which supplies a 12 volt gel battery. Once loaded, the battery will run a 12 volt compressor. The battery and compressor are both well hidden inside the motor compartment.



TRICYCLE FOR MOBILUX 11



CONTROL PANEL

| TRICYCLE | |
|---|---------------|
| Dimensions of package:(WxDxH) | 60x80x150 cm |
| Weight of package (kg) | 30 |
| Dimensions unpacked (WxDxH) (Incl. freezer) | 210x90x118 cm |
| FEATURES: | |
| Handbrake | Yes |
| Internal brake | Yes |
| Internal gears, pcs | 3 |



MOBILUX 11 FREEZER WITH SCOOP CONTAINER

FEATURES

- Low service costs
- Long life
- Combi version of cooler and freezer
- Accessories including baskets - see page 62
- Graphics (option)

| | MOBILUX 11 | MOBILUX 21 |
|--|-------------|--------------|
| Climate class 4 | 4 | 4 |
| Ambient temperature range | +16 to +30 | +16 to +30 |
| Climate class 5 | 5 | n/a |
| Ambient temperature range | +16 to +43 | - |
| Gross volume, litres | 144 | 249 |
| Net volume, litres | 117 | 206 |
| Temperature range inside unit | -18 or +4 | -18 or +4 |
| Standard refrigerant | R290 | R290 |
| Energy consumption / 24 h. Climate class 4 (kwh) 60 % running time | 0,9 | 1,2 |
| Input power for R290 (watt) | 59 | 83 |
| DIMENSIONS | | |
| External dimensions (WxDxH) | 724*654*916 | 1054*654*916 |
| Internal dimensions (WxDxH) | 520*450*686 | 850*450*686 |
| Dimension A | 724 | 1054 |
| Dimension B | 654 | 654 |
| Dimension C | 916 | 916 |
| Dimension D | 780 | 780 |
| Dimension E | 520 | 850 |
| Dimension F | 320 | 650 |
| Dimension G | 450 | 450 |
| Dimension H | 686 | 686 |
| Dimension J | 436 | 436 |
| Dimension L | 846 | 846 |
| Insulation (mm) | 100 | 100 |
| ACCESSORIES | | |
| Max. number of baskets | 1 | 2 |
| Scoop baskets available | Yes | n/a |
| Castors | Incl. | Incl. |
| Castors w. brakes | Optional | Optional |
| Charger and battery included | Yes | Yes |
| Lock | Yes | Yes |
| Thermometer | Optional | Optional |
| Internal light | n/a | n/a |
| OTHER DATA | | |
| Outer cabinet | White | White |
| Inner cabinet | Aluminium | Aluminium |
| Graphics | Optional | Optional |
| Type of cooling | Static | Static |
| Type of defrost | Manual | Manual |
| Power | 220V/50Hz | 220V/50Hz |
| Power 110volt / 60 hz | Optional | Optional |
| Thermostat | Mechanical | Mechanical |
| Net weight, kg | 55 | 68 |
| Gross weight, kg | 62 | 75 |
| SHIPPING | | |
| 20' cont. Capacity | 42 | 30 |
| 40' cont. Capacity | 90 | 64 |
| Standard Trailer capacity | 102 | 74 |

*FOR DIMENSIONS SEE PAGE 19