





NUEVO DISEÑO - NEW DESIGN



CDGO 06 M1
CDGO 06 M2
CDGO 09 M1
CDGO 09 M2
CDGO 12 M1
CDGO 12 M2
CDGO 15 M1
CDGO 15 M2
CDGO 18 M1
CDGO 18 M2
CDGO 25 M1
CDGO 25 M2
CDGO 31 M1
CDGO 31 M2



CDSO 06 M1
CDSO 06 M2
CDSO 09 M1
CDSO 09 M2
CDSO 12 M1
CDSO 12 M2
CDSO 15 M1
CDSO 15 M2
CDSO 18 M1
CDSO 18 M2
CDSO 25 M1
CDSO 25 M2
CDSO 31 M1
CDSO 31 M2

* consultar- consult

Modelo	Longitud (con costados)	Área estantes refrigerados m ²	Superficie total exposición (TDA)	Volumen neto (L)	Estantes	Puertas	Potencia frigorífica HFC / HC	Consumo nominal HFC / HC	Refrigerante HFC / HC
Model	Length (with sides)	Refrigerated shelf area m ²	Total display area (TDA)	Net volume (L)	Shelves	Doors	Cooling capacity HFC / HC	Nominal Power HFC / HC	Refrigerant HFC / HC
MODELOS CON PUERTAS / MODELS WITH DOORS									
CDGO 06 M1-M2	685	1,00	0,69	218	4	1	817	634	1301 806 R-449A R-290*
CDGO 09 M1-M2	998	1,50	0,99	326	4	2	1214	967	1671 1127 R-449A R-290*
CDGO 12 M1-M2	1310	2,00	1,37	434	4	2	1214	1058	1674 1183 R-449A R-290*
CDGO 15 M1-M2	1623	2,50	1,76	543	8	2	2056	1419	1966 1401 R-449A R-290*
CDGO 18 M1-M2	1935	3,00	2,06	652	8	3	2056	1688	2041 1585 R-449A R-290*
CDGO 25 M1-M2	2560	4,00	2,75	869	8	4	2492	2170	3091 2099 R-449A R-290*
CDGO 31 M1-M2	3185	5,00	3,52	1086	16	4	4112	2838	3932 2579 R-449A R-290*
MODELOS SIN PUERTAS / MODELS WITHOUT DOORS									
CDSO 06 M1-M2	685	1,00	0,80	218	4	-	1214	-	1559 - R-449A -
CDSO 09 M1-M2	998	1,50	1,20	326	4	-	1497	-	1797 - R-449A -
CDSO 12 M1-M2	1310	2,00	1,60	434	4	-	1497	-	1800 - R-449A -
CDSO 15 M1-M2	1623	2,50	2,00	543	8	-	2874	-	2937 - R-449A -
CDSO 18 M1-M2	1935	3,00	2,40	652	8	-	2874	-	2968 - R-449A -
CDSO 25 M1-M2	2560	4,00	3,20	869	8	-	2994	-	3600 - R-449A -
CDSO 31 M1-M2	3185	5,00	4,00	1086	16	-	5748	-	5874 - R-449A -

características técnicas y constructivas sujetas a variación sin previo aviso

we reserve the right to change specifications without prior notice

- Modelo CDS: Cortina de noche manual y frente cuba inferior de metacrilato
- Modelo CDG: Puertas batientes sin marco, frontal completo de cristal con serigrafía reducida, apertura máxima 93° y bloqueo de apertura manual. Autocierra con barra de torsión de gran durabilidad, reduce el consumo energético
- Costados de 30 mm, de serie en ABS color gris, opcional CERRADO al mismo precio
- Costado panorámico (doble cristal) opcional con incremento de precio
- Decoración estándar exterior (franja inferior, superior y laterales) en gris RAL 7040
- Decoración opcional, según costados, sólo frontal (franja superior e inferior) o total a elegir en los colores disponibles. Interior en color blanco RAL 9003
- Evaporador ventilado con recubrimiento EPOXI anticorrosión
- Estantes regulables en altura y ángulo, con portaprecios de 40 mm incluidos
- Desescarche natural del evaporador con bandeja de evaporación automática
- Ventiladores electromecánicos, opcional electrónicos (consultar)
- Control electrónico
- Iluminación LED 24v 4000k
- Temperatura de producto, según EN-ISO-23953:
 - M1: -1*+5°C, apropiado para carnes.
 - M2: -1*+7°C, apropiado para lácteos, delis y embutidos
- Clase climática 3 (25°C, 60 H.R)
- Modelos preinstalación incorporan valvulera solenoide y expansión en R-449A, opción R-134a (consultar otros refrigerantes)
- Aislamiento de poliuretano inyectado, densidad 40kg/m3 bajo GWP y cero efecto ODP
- El paragolpes de tubo es opcional en todos los modelos (no incluido de serie)

- CDS Model: Manual night blind and and inferior exposition deck perspex
- CDG Model: Frameless hinged doors with complete glazed frontal with reduced serigraphy, max opening 93° with manual blocking closure. Self-closing with high durability torsion bar, ensure energy savings
- 30 mm sides, standard in gray ABS, optional BLIND at the same price
- Panoramic side (double glass) optional with price increase
- Standard exterior decoration (lower, upper and side stripes) in gray RAL 7040
- Optional decoration, depending on the sides, only front (upper and lower strip) or total to choose in the available colors. Interior in RAL 9003 white
- Ventilated evaporator EPOXY with anticorrosive coating
- Adjustable shelves in height and angle, with 40 mm price holders included
- Natural defrost of evaporator with a utomatic evaporation tray
- Electromechanic fans, on demmand, electronics (consult)
- Electronic control
- 24v LED 4000k lighting
- Product temperature, according to EN-ISO-23953:
 - M1: -1*+5°C, suitable for meat
 - M2: -1*+7°C, suitable for dairy products, delis and sausages
- Climatic class 3 (25°C, 60 H.R)
- Pre-installation models incorporate solenoid and expansion valves in R-449A, option R-134a (consult other refrigerants)
- Injected polyurethane insulation, density 40kg / m3 low GWP and zero ODP effect
- The tube bumper is optional on all models (not included as standard)

Modelo	decoración FRONTAL FRONT decor	decoración TOTAL FRONT decor	Juego costados panorámico	Decoración interior epoxy negro	Paragolpes tubo inox	Iluminación LED X nivel estantes	Separador producto	Pre instalación
Model	normal alto brillo glossy	normal alto brillo glossy	Panoramic sides SET LE	Black interior epoxy decoration normal	Stainless steel bumper ud	LED Lighting X shelves level	product divider	Remote Unit



Lateral PLÁSTICO de serie
PLASTIC side as standard



Lateral CERRADO -LC opcional
BLIND side -LC on demand



Lateral PANORÁMICO -LE opcional
PANORAMIC side -LE on demand

CDGO 12
Acabado exterior decoración total opcional
Total exterior finishing as extra