



Ventilated Refrigeration  
 Semihermetic Compressor 20G und 24G  
 Hermetischer Compressor for 12G  
 Automatic Defrosting with Reverse Cycle System  
 2 Evaporators  
 Heated Frontglas Double and Airchambered  
 Heated Sideglasses  
 with Castors  
 Temperature Range : -12°C/ -22°C  
 with Curtain in the Back  
 Refrigerant : R 452A  
 Panels in RAL 9016 white

## NEO 12G

Length x depth x height	Power supply	Totalpower	Totalpower at Defrosting	Compressorpower <small>( at - 30°C Condensingtemperature )</small>
1165x1140x1285mm	230V / 1 / 50 Hz	2100W	2200W	1090W
Nettweight	Bruttweight	Refrigerant	Defrosting	Defrosting type
260 kg	290 kg	R 452A	Automatic	Reverse Cycle

## NEO 20G

Length x depth x height	Power supply	Totalpower	Totalpower at Defrosting	Compressorpower <small>( at - 30°C Condensingtemperature )</small>
1820x1140x1285mm	400V / 3 / 50 Hz	3000W	3200W	1600W
Nettweight	Bruttweight	Refrigerant	Defrosting	Defrosting type
370 kg	400 kg	R 452A	Automatic	Reverse Cycle

## NEO 24G

Length x depth x height	Power supply	Totalpower	Totalpower at Defrosting	Compressorpower <small>( at - 30°C Condensingtemperature )</small>
2195x1140x1285mm	400V / 3 / 50 Hz	3420W	3820W	1860W
Nettweight	Bruttweight	Refrigerant	Defrosting	Defrosting type
440 kg	470 kg	R 452A	Automatic	Reverse Cycle